

TOWING RECOMMENDATIONS - 20+2 10K CAR HAULER

TRAILER SPECIFICATIONS

Deck Size: 20 ft flat plus 2 ft dovetail

GVWR: 10,000 lbs

Empty Weight: approximately 2,000 to 2,800 lbs

Payload Capacity: approximately 7,200 to 8,000 lbs

TOW VEHICLE REQUIREMENTS

- Tow vehicle rated to tow at least 10,000 lbs
- Equipped with electric brake controller
- Recommended: 3/4 ton or 1 ton truck (F-250, Ram 2500, Silverado 2500)

HITCH AND TONGUE

- Use Class IV or V hitch receiver
- Adjust hitch height to keep trailer level
- Maintain 10 to 15 percent of total trailer weight on tongue

BRAKING AND SAFETY

- Verify trailer brakes work on both axles
- Use breakaway safety switch with charged battery
- Cross safety chains under tongue
- Confirm all wiring and lights are functional

LOADING GUIDELINES

- Load vehicle or cargo slightly forward of center
- Secure load with four tie-down points minimum
- Do not exceed trailer axle ratings or GVWR

DRIVING TIPS

- Allow extra stopping distance
- Take wide turns
- Reduce speed, especially on grades
- Check load security during travel